

# N39/530E.M3

Cylindrical Roller Bearings (single row, with cage)



## Details:

### Main dimensions

|             |       |                       |         |
|-------------|-------|-----------------------|---------|
| d [mm]      | 530   | d <sub>1</sub> [mm]   | ≈ 594.2 |
| D [mm]      | 710   | r <sub>1,2</sub> [mm] | 5       |
| B [mm]      | 136   | r <sub>3,4</sub> [mm] | 5       |
| Weight [kg] | ≈ 155 | s [mm]                | 6.9     |
| E [mm]      | 671   |                       |         |



### Mating dimensions

### Calculation data

|                         |     |                                      |      |
|-------------------------|-----|--------------------------------------|------|
| d <sub>a,min</sub> [mm] | 548 | C [kN]                               | 2780 |
| D <sub>b,min</sub> [mm] | 675 | C <sub>0</sub> [kN]                  | 6350 |
| D <sub>c,max</sub> [mm] | 667 | C <sub>u</sub> [kN]                  | 512  |
| r <sub>a,max</sub> [mm] | 4   | n <sub>th</sub> [min <sup>-1</sup> ] | 436  |
| r <sub>b,max</sub> [mm] | 4   | n <sub>g</sub> [min <sup>-1</sup> ]  | 980  |