

32312B

Kegelrollenlager (einreihig, metrisch)



Details:

| Hauptabmessungen | | | |
|------------------|-------|-----------------------|--------|
| d [mm] | 60 | B [mm] | 46 |
| D [mm] | 130 | d ₁ [mm] | ≈ 96,4 |
| T [mm] | 48,5 | r _{1,2} [mm] | 3 |
| Gewicht [kg] | ≈ 3,1 | r _{3,4} [mm] | 2,5 |
| | | a [mm] | ≈ 38,7 |
| C [mm] | 37 | | |



| Anschlussmaße | | Berechnungsdaten | |
|-------------------------|------|--------------------------------------|------|
| d _{a,max} [mm] | 71 | C [kN] | 230 |
| d _{b,min} [mm] | 72 | C ₀ [kN] | 319 |
| D _{a,min} [mm] | 100 | C _u [kN] | 36,3 |
| D _{a,max} [mm] | 118 | n _{th} [min ⁻¹] | 3978 |
| D _{b,min} [mm] | 122 | n _g [min ⁻¹] | 5800 |
| C _{a,min} [mm] | 6 | e | 0,55 |
| C _{b,min} [mm] | 11,5 | Y | 1,1 |
| r _{a,max} [mm] | 3 | Y ₀ | 0,6 |
| r _{b,max} [mm] | 2,5 | | |