

# NCF2232V

Zylinderrollenlager (einreihig, vollrollig)



## Details:

### Hauptabmessungen

|              |        |                       |          |
|--------------|--------|-----------------------|----------|
| d [mm]       | 160    | d <sub>1</sub> [mm]   | ≈ 208,7  |
| D [mm]       | 290    | D <sub>1</sub> [mm]   | ≈ 251,94 |
| B [mm]       | 80     | r <sub>1,2</sub> [mm] | 3        |
| Gewicht [kg] | ≈ 23,1 | r <sub>3,4</sub> [mm] | 3        |
| E [mm]       | 266,34 | s [mm]                | 6        |



| Anschlussmaße            |     | Berechnungsdaten                     |      |
|--------------------------|-----|--------------------------------------|------|
| d <sub>a, min</sub> [mm] | 174 | C [kN]                               | 990  |
| d <sub>c, min</sub> [mm] | 207 | C <sub>0</sub> [kN]                  | 1490 |
| D <sub>a, max</sub> [mm] | 276 | C <sub>u</sub> [kN]                  | 160  |
| D <sub>b, max</sub> [mm] | 276 | n <sub>th</sub> [min <sup>-1</sup> ] | 948  |
| r <sub>a, max</sub> [mm] | 2,5 | n <sub>g</sub> [min <sup>-1</sup> ]  | 1400 |
| r <sub>b, max</sub> [mm] | 2,5 |                                      |      |