

# NCF3030V



Zylinderrollenlager (einreihig, vollrollig)



## Details:

### Hauptabmessungen

|              |        |                       |         |
|--------------|--------|-----------------------|---------|
| d [mm]       | 150    | d <sub>1</sub> [mm]   | ≈ 170   |
| D [mm]       | 225    | D <sub>1</sub> [mm]   | ≈ 197,6 |
| B [mm]       | 56     | r <sub>1,2</sub> [mm] | 2,1     |
| Gewicht [kg] | ≈ 7,31 | r <sub>3,4</sub> [mm] | 1,5     |
| E [mm]       | 206,8  | s [mm]                | 7       |



| Anschlussmaße            |     | Berechnungsdaten                     |      |
|--------------------------|-----|--------------------------------------|------|
| d <sub>a, min</sub> [mm] | 160 | C [kN]                               | 465  |
| d <sub>c, min</sub> [mm] | 168 | C <sub>0</sub> [kN]                  | 720  |
| D <sub>a, max</sub> [mm] | 215 | C <sub>u</sub> [kN]                  | 82,4 |
| D <sub>b, max</sub> [mm] | 215 | n <sub>th</sub> [min <sup>-1</sup> ] | 1372 |
| r <sub>a, max</sub> [mm] | 2,1 | n <sub>g</sub> [min <sup>-1</sup> ]  | 1800 |
| r <sub>b, max</sub> [mm] | 1,5 |                                      |      |